

MATERIAL SAFETY DATA SHEET

Distributor

SUMMIT TRADE PTE LTD
9/F Baiyun Riverscape Tower, 5 Xijiang 2nd Road,
Wuzhou, Guangxi, China (543001)
Last updated: July 2020

Product identification

Product name: PINE OIL
CAS NO. 8002-09-3
Synonyms: fir oil, terpentinoel, unipine
Formula: C₁₀H₁₈O
Molecular weight: unspecified

Composition/information on ingredients

Typical value: mixture of terpene alcohols (C₁₀H₁₇OH)
70%, terpene hydrocarbons (C₁₀H₁₆) 15%, other
components 15%.

Hazards identification

Eye: Contact with eyes may cause severe irritation, and possible eye burns.
Skin: Causes skin irritation. May cause skin sensitization, an allergic reaction.
Ingestion: Causes gastrointestinal irritation with nausea, vomiting and diarrhea. May cause kidney damage. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea.
Inhalation: May cause respiratory tract irritation.

First aid measures

Eyes: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.
Skin: Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid if irritation develops or persists.
Ingestion: Do not induce vomiting. Get medical aid.
Inhalation: Get medical aid immediately. Remove from exposure and move to fresh air immediately. If not or difficult breathing, give artificial respiration or oxygen.

Fire fighting measures

Extinguishing Media: Use water fog, dry chemical, carbon dioxide, or regular foam.
Other Information: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. As flammable Liquid, it can release vapors that form explosive mixtures at temperatures above the flashpoint.

Accidental release measures

Absorb with inert material (eg vermiculite, sand or earth), then place in suitable container. Use a spark-proof tool.

Handling and storage

Handling: Use only in a well-ventilated area. Ground and bond containers when transferring material. Do not

pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames.
Storage: Keep away from sources of ignition. Store in a cool place in the original container and protect from sunlight. Store in a tightly closed container

Exposure controls/Personal protection

ACGIH: 20 ppm TWA
NIOSH: 100 ppm TWA; 560 mg/m³ TWA 800 ppm IDLH
OSHA - Final PELs: 100 ppm TWA; 560 mg/m³ TWA
Eyes: Wear chemical splash goggles.
Skin: Wear appropriate gloves to prevent skin exposure.
Respirators: If exposure limits are exceeded.

Physical and chemical properties

Alcohol content: 70% min.
Appearance: transparent liquid
Color (Specie Number): 6 max.
Moisture: 1% max.
Specific gravity (20 deg C): 0.900 min.
Flash point: 73-86 degree C

Stability and reactivity data

Acids or acidic material and strong oxidizing agents.
Stability condition to avoid: material can undergo auto oxidation in air & generate heat which can build up in confined spaces causing spontaneous combust.
Hazardous decomposition products: carbon monoxide and/or carbon dioxide.

Toxicological information

Toxicological Information: 1985-86 TOXICITY DATA.
Rabbit, Skin: 500 mg administered for 24 hr produces severe irritation.
Man, oral, TDLO: 4700 mg/kg ingested produces behavioral changes (excitement, ataxia (loss of muscular coordination), headache).

Ecological information

Ecotoxicity: n/a
Environmental: n/a
Other: May be toxic to aquatic organisms; May cause long-term adverse effects in the aquatic environment.

Disposal considerations

Dispose of container and unused contents in accordance with federal, state and local requirements.

Transport Information

IMO hazard Class: 3.3 UN No: 1272. Packing group: III

Regulatory Information

MSDS collection references.

Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.